

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, Australian WorkSafe, Japanese Standard JIS Z 7250:2000, and EU REACH Regulations

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** **CARTRIDGES, EJECTION (Impulse)**  
**CAS Number:** Mixture – Metal Alloy  
**Synonyms:** Impulse Cartridge; EC863-1A-1W; EC446-1A-1W; EC446-1B  
**Product Use:** Medium Caliber Gas Generating Cartridge  
**U.N. Number:** UN 0276  
**U.N. Dangerous Goods Class** Explosive, 1.4C  
**Manufacturer:** Olin Corporation – Winchester Division, Inc.  
**Manufacturers' Address:** 600 Powder Mill Road, East Alton, IL 62024 [www.winchester.com](http://www.winchester.com)  
**Emergency Telephone Number:** US/Canada: 1-800-424-9300  
Outside US/Canada: 703-527-3887  
**MSDS Control Group:** 618-258-3507 (Technical Information Only)

Olin MSDS No.: 00078.0001

Issue Date: 06/01/15

Revision Date: 01/31/2017

Revision No.: 2

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: EXPLOSIVE. KEEP AWAY FROM HEAT. DO NOT SUBJECT TO MECHANICAL SHOCK. PARTICLES FROM FIRING MAY BE HARMFUL IF INHALED. DO NOT TAKE INTERNALLY.

US DOT SYMBOLS



CANADA (WHMIS) SYMBOLS

This Product is not subject to WHMIS

Class 6 Explosive

GHS HAZARD SYMBOLS





<b><u>GHS Classifications:</u></b>	Explosive Division 1.4 STOT RE Category 1 Reproductive Toxicity Category 1A Aquatic Environment, Chronic II
<b><u>Signal Word:</u></b>	Danger
<b><u>Hazard Statements:</u></b>	H204: Fire or projection hazard H372: Causes damage to nervous system, kidney, and hematopoietic system through prolonged or repeated exposure H360: May damage fertility or the unborn child H411: Toxic to aquatic life with long lasting effects
<b><u>Target organs:</u></b>	Nervous, renal and hematopoietic systems
<b><u>Precautionary Statements:</u></b>	P102: Keep out of reach of children P210: Keep away from heat/sparks/open flame/hot surfaces P250: Do not subject to shock/friction P260: Do not breathe dust/fume/gas/mist/vapors/spray P264: Wash hands thoroughly after handling P270: Do not eat, drink or smoke when using this product P271: Use only outdoors or in a well-ventilated area P273: Avoid release to the environment P280: Wear protective gloves/protective clothing/eye protection/face protection
<b><u>GHS Pictograms:</u></b>	Explosive; Pictogram: exploding bomb Specific Target Organ Toxicity; Pictogram Code: GHS08 Environment; Pictogram Code: GHS09
<b><u>EU Classifications:</u></b>	
Hazard Symbols	E, T, N
Risk Phrases	R2: Risk of explosion by shock, friction, fire or other sources of ignition R48: Danger of serious damage to health by prolonged exposure R60: May impair fertility R63: Possible risk of harm to the unborn child R51/53: Toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment
Safety Phrases	S2: Keep out of reach of children S15: Keep away from heat S20/21: When using do not eat, drink or smoke S22: Do not breathe dust S39: Wear eye/face protection S51: Use only in well-ventilated areas S61: Avoid release to the environment

### Health Hazards or Risks From Exposure

This product is composed of a metal capsule which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the product is fired, a small amount of particles may be generated which may be slightly irritating to the eyes and the respiratory tract. The particles may contain trace amounts of these harmful substances:

**Lead:** Ingestion of large amounts of lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to lead can cause kidney damage, anemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function.

**Nitroglycerin:** Will produce dilation of blood vessels and drop in blood pressure which may affect the heart. It has also been shown to cause methemoglobinemia (cyanosis).

**Copper:** Inhalation of high concentrations of metallic copper dusts or fumes may cause nasal irritation and/or nausea, vomiting and stomach pain.

**Potassium nitrate:** Ingestion of large doses of potassium nitrate can lead to the development of methemoglobinemia (inability of the blood to carry sufficient oxygen).

It is unlikely that the amount of particles that someone would be exposed to from firing would be sufficient to cause any of these effects.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Product consists of the following components: A) Shell Case; B) Electric Primer; C) Wad (either Nitrocellulose or Mylar); D) Smokeless Base Powder; and E) Double Base Powder.

Components	% By Weight	CAS Number	EINECS/ ELINCS #
Aluminum	57 -74	7429-90-5	231-072-3
Copper	1 – 6	7440-50-8	231-159-6
Nitrocellulose	1 - 6	9004-70-0	Polymer
Nitroglycerin	0 - 5	55-63-0	200 – 240 -8
Potassium nitrate	> 1	7757-79-1	231-818-8
Lead styphnate	0.1 – 0.5	15245–44–0	239–290-0
Basic lead styphnate	0.1 – 0.5	12403-82-6	235-642-2
<b>Wad (used in the Impulse Cartridge or EC863-1A-1W or EC446-1A-1W Cartridge)</b>			
Nitrocellulose	1 - 2.5	9004-70-0	Polymer
<b>Wad (used in the EC446-1B Cartridge)</b>			
Polyethylene terephthalate	2.5	25038-59-9	Polymer

### 4. FIRST AID MEASURES

**Eye Contact:** Immediately flush out fume or particles with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If eye irritation develops, call a physician at once.

**Skin Contact:** Wash skin with plenty of soap and water.

**Inhalation:** If symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention.

**Ingestion:** If ingested, immediately call a physician.

#### Medical Conditions Aggravated By Exposure:

There are no medical conditions known to be aggravated by exposure to this product in its solid form. Exposure to lead can aggravate anemia, cardiovascular and respiratory disease.

#### Recommendations To Physicians:

Remove from exposure, if possible, and treat symptoms

### 5. FIRE FIGHTING MEASURES

PROPERTY	VALUE	PROPERTY	VALUE
Explosive	Yes	Flammable	Not applicable
Combustible	Not applicable	Pyrophoric	No
Flash Point (°C):	Not applicable	Burning Rate of Material:	Not applicable
Lower Explosive Limit:	Not applicable	Autoignition Temp.:	288 °C (550 °F)
Upper Explosive Limit:	Not applicable	Flammability Classification: (defined by 29 CFR 1910.1200)	Explosive

Unusual Fire and Explosion Hazards:Extinguishing Media:Special Firefighting Procedures:

Possible projection hazard.


Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used.


Do not fight fire when fire reaches cargo. Cargo may explode.

Firefighters must wear self-contained breathing apparatus (SCBA) and full protective equipment. Structural firefighters' protective clothing will only provide limited protection.

Isolate materials not yet involved in the fire. Move containers from fire area if possible; otherwise, cool with carefully applied water spray.

Prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas, if practical.

**NFPA RATING SYSTEM****HMIS RATING SYSTEM**

HEALTH HAZARD (BLUE)		0*	
FLAMMABILITY HAZARD (RED)		1	
PHYSICAL HAZARD (YELLOW)		2	
<b>PROTECTIVE EQUIPMENT</b>			
EYES	PPE CODE	RESPIRATORY	HEARING
	A	See Sect 8	See Sect 8

**Hazard Scale:** 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## 6. ACCIDENTAL RELEASE MEASURES

**FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEM TREC AT 800-424-9300.**

Spill Response:

A spill of this material will normally not require emergency response team capabilities. If, however, a large spill occurs, call 1-888-289-1911 for technical assistance.

Accidental Release Procedures:

Spills of this material should be handled carefully. Do not subject materials to mechanical shock. Collect material and place in a designated, labeled waste container. See Section 13 for waste disposal.

## 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Workers should wash hands thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored.

Conditions for Safe Storage:

Store in accordance with local regulations. Store in original containers in a cool, dry location at temperatures below 130 °F. Product has an indefinite shelf life if stored at 50-90 °F and 35% relative humidity. Store away from Acids, Class A & B explosives, strong oxidizers, and caustics. Avoid mechanical impact or shock and electrical discharge.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:

CAS #	CHEMICAL NAME	ACGIH TLV	OSHA PEL	INTERNATIONAL OELS
7429-90-5	Aluminum	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup> (total dust); 5 mg/m <sup>3</sup> (resp. fraction)	Belgium, France, Hungary, Sweden – 5 mg/m <sup>3</sup> (resp. dust) Germany, Switzerland – 6 mg/m <sup>3</sup> Denmark, Netherlands, U.K. – 10 mg/m <sup>3</sup>
7440-50-8	Copper	0.2 mg/m <sup>3</sup> (fume), 1 mg/m <sup>3</sup> (dusts and mists)	0.1 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dusts and mists)	Austria, Belgium, Canada: 0.2 mg/m <sup>3</sup> (fumes), 1 mg/m <sup>3</sup> (dusts) Denmark: 1.0 mg/m <sup>3</sup> (dust and powder) Germany (MAK): 0.1 mg/m <sup>3</sup> (fume), 1 mg/m <sup>3</sup> (dusts and mists)
9004-70-0	Nitrocellulose	None established	None established	None established
55-63-0	Nitroglycerin	0.05 ppm (0.46 mg/m <sup>3</sup> ) Skin	Ceiling – 0.2 ppm (2 mg/m <sup>3</sup> ) Skin	Denmark: 0.02 ppm (0.2 mg/m <sup>3</sup> ) Norway, Sweden: 0.03 ppm (0.3 mg/m <sup>3</sup> ) Austria, Belgium, Germany, The Netherlands, Poland, Switzerland: 0.05 ppm (0.47 mg/m <sup>3</sup> ), skin Finland, France: 0.1 ppm (0.9 mg/m <sup>3</sup> ), skin U.K.: 0.2 ppm (2 mg/m <sup>3</sup> ), skin
7757-79-1	Potassium nitrate	None established	None established	None established
15245-44-0	Lead styphnate	None established	None established	None established
12403-82-6	Basic lead styphnate	None established	None established	None established
25038-59-9	Polyethylene terephthalate	None established	None established	Russia: 5 mg/m <sup>3</sup>

Engineering Controls:

Local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use general exhaust ventilation. Use explosion-proof ventilation.

Respiratory Protection:

Not normally needed. Maintain airborne contaminant concentrations below guidelines listed above. Use an appropriate approved air-purifying respirator equipped with HEPA cartridges/canisters where there is the potential for exceeding established occupational exposure limits.

Eye/Face Protection:

Use safety glasses.

Hand Protection:

Not normally needed

Skin Protection:

Not normally needed.

Hearing Protection:

Not normally needed. During firing use hearing protection.

General Hygiene:

Do not eat, drink, or smoke while using this product. Wash hands thoroughly after use.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

PROPERTY	VALUE	PROPERTY	VALUE
Appearance:	Headed aluminum cylinder	Physical State:	Solid
Odor:	None	Odor Threshold:	None
Boiling Point (°F):	Not applicable	Melting point:	Not applicable
Vapor Pressure (mm Hg):	Not applicable	Freezing point:	Not applicable
Vapor Density (air = 1):	Not applicable	Bulk Density:	Not applicable
Specific gravity (g/cc):	Not applicable	Viscosity (cps):	Not applicable
pH:	Not applicable	Decomposition Temperature:	Not applicable
Solubility in Water (20 °C):	Insoluble	Evaporation Rate:	Not applicable
Volatiles, Percent by volume:	Not applicable	Octanol/water partition coefficient:	Not applicable

**10. STABILITY AND REACTIVITY**Stability:

Stable under normal temperatures and pressure.

Possibility of Hazardous Reactions:

Hazardous polymerization will not occur

Incompatible Materials:

Acids, Class A &amp; B explosives, strong oxidizers, and caustics

Hazardous Decomposition Products:

Nitrogen oxides, carbon monoxide, lead oxides, carbon dioxide, lead dust/fume

Conditions to Avoid:

Contact with incompatible materials. Physical damage to containers; cartridges may detonate if case is punctured.

**11. TOXICOLOGICAL INFORMATION**Potential Routes of Entry: Inhalation, Skin, and by Ingestion.

The physical nature of this product makes absorption from any route unlikely. A small amount of inhalable particles may be created when cartridge is fired.

Effects Of Acute Exposure:

PRODUCT		SELECTED COMPONENTS					
		Basic lead styphnate	Lead styphnate	Nitroglycerin	Copper	Potassium nitrate	Aluminum
Inhalation LC <sub>50</sub>	Particles generated from firing may be slightly toxic	No data	No data	No data	No data	No data	> 1,000 mg/m <sup>3</sup> , 4 h (rat)
Skin Contact LD <sub>50</sub>	Skin absorption unlikely	No data	No data	> 280 mg/kg (rabbit)	375 mg/kg, sc (rabbit)	No data	No data
Ingestion LD <sub>50</sub>	Ingestion unlikely	No data	No data	105 mg/kg (rat)	3.5 mg/kg, ip (mouse)	3,750 mg/kg (rat)	No data
Irritation	Particles generated from firing may be slightly irritating to the eyes	No data	No data	Mild eye and skin irritant	Respiratory irritant	No data	Mild eye and skin irritant
Sensitization	Sensitization to this Product has not been reported	No data	No data	No data	No data	No data	No data

Other Adverse Effects:Target Organ Toxicity:

No reported target organ toxicity from this product. Lead has caused nervous system, kidney and hematopoietic system damage in humans and laboratory animals.

Reproductive Toxicity:

This product is not known or reported to cause reproductive effects. Lead has been shown to reduce male reproductive function in humans and laboratory animals.

<u>Teratogenicity (Birth Defects):</u>	This product is not known or reported to cause developmental toxicity. Lead has been shown to affect fetal development including birth defects.
<u>Mutagenicity:</u>	This product is not known or reported to be mutagenic. Lead has been shown to be mutagenic in several <i>in vitro</i> assays.
<u>Carcinogenicity:</u>	This product is not listed as a carcinogen by OSHA, NTP or IARC. IARC lists lead as possibly carcinogenic to humans, group 2B.

## 12. ECOLOGICAL INFORMATION

### Environmental Effects:

PRODUCT: Product has not been tested for environmental properties.

### COMPONENTS:

<u>Copper:</u>	Copper concentrations from 0.1 to 1.0 mg/l have been found to be not toxic for most fish. However, concentrations of 0.015 to 3.0 mg/l have been reported as toxic, particularly in soft water to many kinds of fish, crustacea, mollusks, insects, and plankton.
<u>Lead:</u>	LC 50 (48 hrs.) to bluegill is reported to be 2-5 mg/l. Lead is toxic to waterfowl.
<u>Nitrocellulose:</u>	LC <sub>50</sub> > 1000 mg/l to fish, invertebrates, and algae.
<u>Nitroglycerin:</u>	LC <sub>50</sub> = 1.228 mg/l to Bluegill, (96 hour, static)

### Environmental Fate:

MOBILITY:	Dissolved lead may migrate through soil.
PERSISTENCE/DEGRADABILITY:	Not biodegradable. May decompose in soil leading to accumulation of lead.
BIOACCUMULATION:	No data

## 13. DISPOSAL CONSIDERATIONS

Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding the treatment, storage and disposal for hazardous and nonhazardous wastes.

## 14. TRANSPORT INFORMATION

### Regulatory Information for US DOT, IATA, IMO, and ADR:

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

<u>Proper Shipping Name:</u>	Cartridges, power device
<u>Hazard Class Number and Description:</u>	Explosive 1.4C
<u>UN Identification Number:</u>	UN 0276
<u>Packing Group:</u>	PGII
<u>DOT Label(s) Required:</u>	Explosive 1.4
<u>Marine Pollutant:</u>	None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

### Additional Information:

North American Emergency Response Guidebook Number (2004): 114

U.S. DEPARTMENT OF TRANSPORTATION SHIPPING REGULATIONS: This product is classified as dangerous goods under 49 CFR 172.101. Note: May be reclassified domestically as an ORM-D if packaged as a consumer commodity per 49 CFR 173.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is classified as Dangerous Goods.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): This product is classified as Dangerous Goods.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: This product is classified as Dangerous Goods.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is classified by the United Nations Economic Commission for Europe to be dangerous goods.

## 15. REGULATORY INFORMATION

### US FEDERAL

TSCA	The components of this product are listed on the Toxic Substance Control Act inventory.				
CERCLA:	Copper, R.Q.* = 5000 lbs.; Nitroglycerin, R.Q. = 10 lbs; Lead, R.Q. = 10 lbs. (No reporting is required if diameter of the pieces of metal is equal to or exceeds 100 micrometers (0.004 inches).				
SARA 313:	Aluminum (fume or dust), Copper, Lead and Lead compounds, Nitroglycerin				
SARA 311/312:	<u>Health:</u>	Acute – No Chronic - No	<u>Fire:</u> No	<u>Reactivity:</u> Yes	<u>Release of Pressure:</u> No
SARA 302 EHS List:	None of the components of this product are listed.				

\*RQ = Reportable Quantity

### STATE RIGHT-TO-KNOW STATUS

Component	California	New Jersey	Pennsylvania	Massachusetts	Michigan
Aluminum	Not listed	X	X	X	Not listed
Copper	Not listed	X	X	X	X
Nitrocellulose	Not listed	X	X	X	Not listed
Nitroglycerin	Not listed	X	X	X	Not listed
Potassium nitrate	Not listed	Not listed	X	X	Not listed
Lead styphnate	X	Not listed	Not listed	X	Not listed
Basic lead styphnate	X	Not listed	Not listed	Not listed	Not listed
Polyethylene terephthalate	Not listed	Not listed	Not listed	Not listed	Not listed

### CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65)

Warning! This product contains detectable amounts of a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm.

### GHS CLASSIFICATION

Explosive Division 1.4  
STOT RE Category 1  
Reproductive Toxicity Category 1A  
Aquatic Environment, Chronic II

### EUROPEAN REGULATIONS

#### Hazard Classification

Danger Symbols: E, T, N  
Risk Phrases: R2, R48, R60, R63, R51/53  
Safety Phrases: S2, S15, S20/21, S22, S39, S51, S61

German WGK Classification: Not known.

### CANADIAN REGULATIONS



DSL/NDSL Inventory: The components of this product are on the DSL  
IDL: Aluminum, Copper, Lead  
CEPA PRIORITIES LIST: None  
WHMIS: This product is not subject to WHMIS. It is regulated as a Class 6 Explosive in Canada.

#### JAPANESE REGULATIONS

Existing National Inventory of Chemical Substances (ENCS): The components of this product are listed

Japanese Priority Assessment Chemical Substances: None of the components of this product are listed

#### OTHER INTERNATIONAL CHEMICAL INVENTORIES

Swiss Giftliste List of Toxic Substances: All Components Listed  
Australian Inventory (AICS): All Components Listed

#### 16. OTHER INFORMATION

REVISIONS: 02

PREPARED BY: Olin Corporation

OTHER: Additional information available from: [www.winchester.com](http://www.winchester.com)

NOTICE: THE INFORMATION IN THIS MSDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. OLIN BELIEVES THIS INFORMATION TO BE RELIABLE AND CURRENT AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS.